# SITE PLAN 9 ROUTE 103 WEST

**ASSESSOR'S MAP 35 LOTS 4-1 & 4-2** 

WARNER, NH 03278
DATE: MAY 06, 2020
REV: JULY 10, 2020


PREPARED FOR:

## COMET, LLC


355 MIDDLESEX AVE, SUITE 7 WILMINGTON, MA 01887

### INDEX OF DRAWINGS


SHEET NO.	DWG NO.	DRAWING TITLE
1.	CS0001	COVER SHEET
2.	CS0002	NOTES AND LEGEND
3.	CS0201	EXISTING CONDITIONS PLAN
4.	CS0202	EXISTING CONDITIONS PLAN -SITE VIEW
5.	CS0501	TRAFFIC CONTROL & DEMO PLAN
6.	CS1001	LAYOUT AND MATERIALS PLAN
7.	CS1501	GRADING AND DRAINAGE PLAN
8.	CS1701	UTILITY PLAN
9.	CS6001	SITE DETAILS
10.	CS6002	SITE DETAILS
11.	CS6021	DRAINAGE DETAILS
12.	CS6022	STORMWATER STORAGE SYSTEM DETAILS
13.	CS6051	UTILITY DETAILS
14.	CS7001	LANDSCAPE & LIGHTING PLAN
15.	CS8001	EROSION AND SEDIMENT CONTROL PLAN
16.	CS8501	EROSION AND SEDIMENT CONTROL DETAILS



LOCUS MAP




USGS MAP N.T.S.



PREPARED BY:

## RANGER ENGINEERING GROUP, INC




Ranger Engineering Group, Inc.

13 Branch Street, Suite 101

Methuen, MA 01844

Tel: 978-208-1762

rangereng.com



WARNER PLANNING BOARD CHAIRMAN:

DATE:

OWNER

Ranger Engineering Group, Inc.
13 Bramch Street, Suite 101
Methuen, MA 01844
Tel: 978-208-1762

ROUTE 10/3 WEST, WARNER NH,

**COVER SHEET** 

CS0001

ASSESSOR'S MAP 35 LOTS 4-1 & 4-2

COMET, LLC 355 MIDDLESEX AVE, SUITE 7 WILMINGTON, MA 01887

DATE: 2020-05-06

TE: SCALE: 2020-05-06

SHEET 1

1 OF 16

CONSTRUCTION NOTES:

1. CONSTRUCTION

EXISTING TOPSOIL AND SUBSOIL SHALL BE REMOVED FROM ROADWAY AND BUILDING AREAS AND STOCKPILED.

B. TREES AND STUMPS:
TREES AND STUMPS SHALL BE REMOVED FROM THE SITE AND DISPOSED OF IN AN APPROVED MANNER. STUMPS SHALL NOT BE BURIED ON SITE.

2. <u>MATERIALS</u>

A. BITUMINOUS CONCRETE PAVEMENT:

PARKING AREAS:
SURFACE COURSE:
WEARING COURSE
BINDER COURSE:
BINDER COURSE

1-1/2 INCHES CLASS I BITUMINOUS CONCRETE PAVEMENT, TYPE I-1
2-1/2 INCHES CLASS I BITUMINOUS CONCRETE PAVEMENT, TYPE I-1

GRAVEL BASE COURSE: 4 INCHES COMPACTED DENSE GRADED CRUSHED STONE FOR SUB-BASE (NH 300.304)

8 INCHES COMPACTED SUB-BASE

B. LANDSCAPE AREAS:
DISTURBED AREAS NOT COVERED BY STRUCTURES OR PAVEMENT AND NOT OTHERWISE
SPECIFIED ON THE LANDSCAPE PLAN SHALL RECEIVE 6 INCHES OF TOPSOIL. THESE AREAS
ARE TO BE SEEDED AND WATERED UNTIL A HEALTHY STAND OF GRASS IS OBTAINED.
LANDSCAPE AREAS ADJACENT TO THE BUILDING SHALL BE FINISHED WITH 3" OF 1-1/2" RIVER
ROCK.

C. TRAFFIC CONTROLS:

ALL SIGNAGE AND PAVEMENT MARKINGS SHALL CONFORM TO THE LATEST EDITION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (M.U.T.C.D.)

D. ADA CONFORMANCE:
ALL HANDICAPPED ACCESSIBLE RAMPS AND SIDEWALKS SHALL BE CONSTRUCTED IN CONFORMANCE WITH THE AMERICANS WITH DISABILITIES ACT (ADA) AND THE STATE OF NEW HAMPSHIRE'S ADA REASONABLE ACCOMMODATION POLICY, WHICHEVER IS, WHICHEVER IS MORE RESTRICTIVE.

4. <u>UTILITIES</u>

**ABBREVIATIONS** 

BITUMINOUS

MINIMUM

NOT TO SCALE

A. EXISTING UTILITIES:
THE LOCATION AND ELEVATIONS OF EXISTING UTILITIES AS SHOWN ON THESE PLANS ARE
BASED ON THE SURVEY NOTED ABOVE AND SHALL BE VERIFIED BY THE CONTRACTOR PRIOR

TO CONSTRUCTION AND PRIOR TO ORDERING STRUCTURES.


B. PRIVATE UTILITIES:
THE LOCATION, SIZE, DEPTH, AND SPECIFICATIONS FOR CONSTRUCTION OF PROPOSED PRIVATE UTILITY SERVICES SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS PROVIDED BY, AND APPROVED BY, THE RESPECTIVE UTILITY COMPANY (GAS, TELEPHONE OR ELECTRIC). FINAL DESIGN AND LOCATIONS AT THE BUILDING WILL BE PROVIDED BY THE ARCHITECT. THE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF THE UTILITY CONNECTIONS WITH THE RESPECTIVE UTILITY COMPANIES PRIOR TO ANY UTILITY CONSTRUCTION OR DEMOLITION.

C. STORM DRAINAGE:
STORM DRAIN PIPING SHALL BE HIGH DENSITY POLYETHYLENE PIPE (HDPE) WITH
CORRUGATED EXTERIOR, SMOOTH LINED (n=0.013) WITH SOIL TIGHT JOINTS UNLESS
OTHERWISE NOTED ON THE GRADING & DRAINAGE PLAN.

D. PROPOSED STRUCTURES:
RIM ELEVATIONS OF PROPOSED DRAINAGE MANHOLES AND ASSOCIATED STRUCTURES ARE APPROXIMATE. FINAL ELEVATIONS. ARE TO BE SET FLUSH AND CONSISTENT WITH THE GRADING PLAN. ADJUST ALL OTHER RIM ELEVATIONS OF MANHOLES, WATER GATES, GAS GATES AND OTHER UTILITIES TO FINISH GRADE WITHIN LIMITS OF WORK.

USE REGULATIONS TABLE							
USES .	TYPES	BY RIGHT	SPECIAL PERMIT -	PARKING			
CONVENIENCE RETAIL ESTABLISMENTS	FOOD, DRUGS, PROPRIETY GOODS	Х		1 SPACE PER 150 SF (50 PARKING SPACES @ 7500 SF)			
GENERAL MERCHANDISE RETAIL	APPAREL, FURNITURE, HARDWARE, DISCOUNT	Х		1 SPACE PER 250 SF (30 PARKING SPACES @ 7500 SF)			
EATING AND DRINKING ESTABLISHMENTS		Х		1 SPACE PER 3 SEATS & 1 SPACE PER EMPLOYEE			
DRIVE IN EATING ESTABLISHMENTS	FAST FOOD		Х	1 SPACE PER 50 SF (150 @7,500 SF) 1 SPACE PER 3 SEATS & 1 PER EMPLOYEE			
HOTEL/MOTEL		Х		1.1 SPACE PER UNIT & 1 SPACE PER 100 SF OF COMMON SPAC & 1 SPACE PER 5 RESTAURANT SEATS			
PERSONAL/CONSUMER SERVICE ESTABLISHMENT		Х					
PROFESSIONAL/BUSINESS OFFICES AND SERVICES		Х	Account of the second of the s	1 SPACE PER 100 SF ( 100 SPACES @10,000 SF)			
MISC. BUSINESS REPAIR SERVICES			Х				
MOVIE THEATER		Х	and the second s				
INDOOR AMUSEMENT/ RECREATION SERVICE			Х				
COMMUNICATIONS/ TELEVISION TOWER	A A ST.		Х				
COMMERCIAL PARKING LOT/STRUCTURE		acinetic committee in	X				
BUS PASSENGER TERMINAL			X				
RESEARCH OFFICES			Х	1 SPACE PER 100 SF (100 SPACES @ 10,000 SF)			
LIGHT INDUSTRIAL FIRM	MACHINE SHOP, COMPUTER, ETC	and established to the stabilish in its size of the mean easy out a road and a sunstruction	Х	1200 31 74 0223 (6) 10,000 31			
PRIVATE DAY CARE			Х				
ACCESSORY BUILDING	PRIVATE POOL, PRIVATE GARAGE, TOOL SHED, ETC	Х	Alled a shired an are an a sans salada, ala armenenin se alabagas andem				
YEAR-ROUND GREENHOUSE/ FARM STAND	AGRICULTURE/FARM PRODUCTS FOR RETAIL SALE		X				
PUBLIC UTILITY		X					
TOWN OWNED UTILITY FACILITY/PLANT	POWER, WATER FILTER, SEWAGE TREATMENT	A CONTRACTOR CONTRACTO	Х				
HOSPITAL/MEDICAL INSTITUTION			X	1 SPACE PER 100 SF ( 100 SPACES @10,000 SF)			
TOWN BUILDING		х	OCCUPATION OF THE PARTY OF THE	( TOO 2) VICES (MIO) OUR 3L)			
PUBLIC PARK		UPA BELLEVINIA A PROCESSI NA APPARAMENTA NA MENONE AND ALLA MANAGEMENTA NA MENONE AND ALLA MANAGEMENTA NA MEN	Х				

CB CATCH BASIN  CONC  CONCRETE  DH DRILL HOLE  DMH DRAIN MANHOLE  ELEV ELEVATION  ESTIMATED SEASONAL HIGH GROUND  WATER  FND FOUNDATION  FES FLARED END SECTION  GF GARAGE FLOOR  HDPE HIGH DENSITY POLYETHYLENE PIPE  HYD HYDRANT  INV INVERT ELEVATION  DEC OVERHEAD ELECTRIC  PC POINT OF CURVATURE  PC PERFORATED  PRC POINT OF REVERSE CURVE-CURVE  PROPOSED  PROPOSED  PT POINT OF TANGENT  PVC POLYVINYL CHLORIDE PIPE  TYP REINFORCED CONCRETE PIPE  TYP TYPICAL  VGC VERTICAL GRANITE CURB  CCB CAPE COD BERM	Diii	DIT OMINOGO	ocs	OUTLET CONTROL STRUCTURE
CONC CONCRETE DH DRILL HOLE DMH DRAIN MANHOLE ELEV ELEVATION PRC PREFORATED PROPOSED WATER  EXIST EXISTING FOUNDATION PRC POINT OF REVERSE CURVE-CURVE PROPOSED PROPO	СВ	CATCH BASIN		
DH DRILL HOLE  DMH DRAIN MANHOLE  ELEV ELEVATION  ESHGW ESTIMATED SEASONAL HIGH GROUND WATER  EXIST EXISTING  FND FOUNDATION  FESS FLARED END SECTION  GF GARAGE FLOOR  HIGH DENSITY POLYETHYLENE PIPE  HYD HYDRANT  INV INVERT ELEVATION  PCC PRECAST CONCRETE CURB  PREF PERFORATED  PROPOSED  PROPOSED  PT POINT OF TANGENT  PVC POLYVINYL CHLORIDE PIPE  RCP REINFORCED CONCRETE PIPE  STR STRUCTURE  TYP TYPICAL  VGC VERTICAL GRANITE CURB  CCB CAPE COD BERM	CONC	CONCRETE		
DMH DRAIN MANHOLE ELEV ELEVATION  ESHGW ESTIMATED SEASONAL HIGH GROUND WATER  EXIST EXISTING  FND FOUNDATION  FESS FLARED END SECTION  GF GARAGE FLOOR  HDPE HIGH DENSITY POLYETHYLENE PIPE  INV INVERT ELEVATION  DRAIN MANHOLE  PERF PERFORATED  PERFORATED  PROPOSED  P	DH	DRILL HOLE	PC	POINT OF CURVATURE
ELEV ELEVATION  PRC POINT OF REVERSE CURVE-CURVE  PROP PROPOSED PR	DMH		PCC	PRECAST CONCRETE CURB
ESHGW ESTIMATED SEASONAL HIGH GROUND WATER  EXIST EXISTING  FND FOUNDATION  FES FLARED END SECTION  GF GARAGE FLOOR  HIGH DENSITY POLYETHYLENE PIPE  HYD HYDRANT  INV INVERT ELEVATION  PROP PROPOSED  PONTATION  POLYING  P			PERF	PERFORATED
WATER  EXIST  EXISTING  FOUNDATION  FOUNDATION  FES  FLARED END SECTION  GF  GARAGE FLOOR  HIGH DENSITY POLYETHYLENE PIPE  HYD  HYD  HYDRANT  INV  INVERT ELEVATION  EXISTING  PVC  POLYVINYL CHLORIDE PIPE  RCP  REINFORCED CONCRETE PIPE  SMH  SEWER MANHOLE  STR  STRUCTURE  TYP  TYPICAL  VGC  VERTICAL GRANITE CURB  CAPE COD BERM	ELEV	ELEVATION	PRC	POINT OF REVERSE CURVE-CURVE
EXIST EXISTING PVC POLYVINYL CHLORIDE PIPE FND FOUNDATION RCP REINFORCED CONCRETE PIPE FES FLARED END SECTION SMH SEWER MANHOLE STR STRUCTURE HIGH DENSITY POLYETHYLENE PIPE HYD HYDRANT INV INVERT ELEVATION CCB CAPE COD BERM	ESHGW		PROP	PROPOSED
FND FOUNDATION FOUNDATION FES FLARED END SECTION GF GARAGE FLOOR HDPE HIGH DENSITY POLYETHYLENE PIPE HYD HYDRANT INV INVERT ELEVATION IP IRON PIPE  PVC POLYVINYL CHLORIDE PIPE RCP REINFORCED CONCRETE PIPE SMH SEWER MANHOLE STR STRUCTURE TYP TYPICAL VGC VERTICAL GRANITE CURB CAPE COD BERM			PT	POINT OF TANGENT
FES FLARED END SECTION  GF GARAGE FLOOR  HDPE HIGH DENSITY POLYETHYLENE PIPE  HYD HYDRANT  INV INVERT ELEVATION  IP IRON PIPE  RCP REINFORCED CONCRETE PIPE  SMH SEWER MANHOLE  STR STRUCTURE  TYP TYPICAL  VGC VERTICAL GRANITE CURB  CCB CAPE COD BERM	EXIST	EXISTING	PVC	POLYVINYL CHLORIDE PIPE
FES FLARED END SECTION  GF GARAGE FLOOR  HIGH DENSITY POLYETHYLENE PIPE  HYD HYDRANT  INV INVERT ELEVATION  IP IRON PIPE  SMH SEWER MANHOLE  STR STRUCTURE  TYP TYPICAL  VGC VERTICAL GRANITE CURB  CCB CAPE COD BERM	FND	FOUNDATION	RCP	REINFORCED CONCRETE PIPE
GF GARAGE FLOOR  HDPE HIGH DENSITY POLYETHYLENE PIPE  HYD HYDRANT  INV INVERT ELEVATION  IP IRON PIPE  STR STRUCTURE  TYP TYPICAL  VGC VERTICAL GRANITE CURB  CCB CAPE COD BERM	FES	FLARED END SECTION	SMH	
HDPE HIGH DENSITY POLYETHYLENE PIPE  HYD HYDRANT  INV INVERT ELEVATION  IP IRON PIPE  TYP TYPICAL  VGC VERTICAL GRANITE CURB  CCB CAPE COD BERM	GF	GARAGE FLOOR		
HYD HYDRANT  VGC VERTICAL GRANITE CURB  INV INVERT ELEVATION  CCB CAPE COD BERM  IP IRON PIPE	HDPE	HIGH DENSITY POLYETHYLENE PIPE	SIR	STRUCTURE
INV INVERT ELEVATION  CCB CAPE COD BERM  IP IRON PIPE	HYD	HYDRANT	TYP	TYPICAL
IP IRON PIPE			VGC	VERTICAL GRANITE CURB
		INVERT ELEVATION	ССВ	CAPE COD BERM
IR IRON ROD	IP	IRON PIPE		
	IR <sup>1</sup>	IRON ROD		
MAX MAXIMUM	MAX	MAXIMUM		



SITE PLAN
ROUTE 103 WEST, WARNER NH,

ASSESSOR'S MAP 35 LOTS 4-1 & 4-2


OWNER

OSGOOD, JR No. 12080

WARNER PLANNING BOARD CHAIRMAN:

COMET, LILC 355 MIDDLESEX AVE, SUITE 7 WILMINGTON, MA 01887

NOTES AND LEGEND CS0002



Ramger Engineering Group, Inc.

13 Branch Street, Suite 101


Metthuen, MA 01844


Tel: 978-208-1762


rangereng.com


TE: SCALE:: 2020-05-06


SHEET 2 OF 16























- SINGLE SOLID LINE WHITE (SSLW) NOTE:
  - 1. ALL MARKINGS SHALL BE WHITE TRAFFIC PAINT. MASS DOT M7.01.23 FAST DRYING WHITE WATER-BORNE TRAFFIC PAINT.
- SINGLE WHITE LINE DETAIL NOT TO SCALE



STRAIGHT




- 1. SYMBOL SHALL BE CENTERED IN THE PARKING STALL AND SHALL BE WHITE.
- 2. PAVEMENT MARKING STRIPES SHALL BE WHITE. (DOUBLE STRIPED - SEE STALL LAYOUT DETAIL) MASS DOT M7.01.23 FAST DRYING WHITE WATER-BORNE TRAFFIC PAINT.
- 3. SYMBOL TO BE PAINTED IN ALL HANDICAP SPACES.
- ACCESSIBLE PARKING SPACE SYMBOL




PLAN VIEW

DUMPSTER PAD NOTES


- 1. SIZE OF DUMPSTER PAD TO BE AS INDICATED ON PLANS.
- 2. CONSTRUCTION JOINTS SHALL BE PLACED NO MORE THAN 40 FEET ON CENTER AND SHALL BE EQUALLY SPACED OVER THE LENGTH AND WIDTH OF PAD.
- 3. ALL HINGES TO BE SELF CLOSING SPRING HINGE FOR A MINIMUM 300 LB GATE CARRYING A 700LB POINT LOAD.
- DUMPSTER PAD WITH ENCLOSURE







- 2. ALL STRIPING SHALL BE 4" WIDE SOLID WHITE PAVEMENT MARKINGS UNLESS OTHERWISE NOTED. MASS DOT M7.01.23 FAST DRYING WHITE WATER-BORNE TRAFFIC
- 3. 8' STALL WIDTH REFERS TO 8' CLEAR BETWEEN INSIDE EDGES OF PAVEMENT


ACCESSIBLE PARKING SPACE
NOT TO SCALE








7/10/2020 FINAL REVIEW COMMENTS DATE REVISIONS SITE PLAN ROUTE 103 WEST, WARNER NH,



SITE DETAILS CS6002



Ramger Engineering Group, Inc. 13 Branch Street, Suite 101 Methuen, MA 01844 Telt 978-208-1762 ramgereng.com

SCALE 2020-05-06

SHEET 10 OF 16


SINGLE-STRIPED PARKING PAVEMENT MARKING


SINGLE-STRIPED PARKING PAVEMENT MARKING

WARNER PLANNING BOARD CHAIRMAN:


DATE:


(WHERE APPLICABLE)







CHBC - CHANNEL BLILL DINGVIOLATA - Warmer NHIDESIGN PLIEB ISHIPL ANSETICSARDA dura DI OTTED: ZARDARDA 4-34 DM DV: Olin Disklad









**EROSION** CONTROL INSTALLED DOWN GRADIENT FLOW PROPOSED STOCKPILE AREA PROVIDE DRAIN SWALE TO DIRECT WATER AWAY FROM PROPOSED STOCKPILE AREA

- 50' (MIN.)

500000000

PLAN VIEW

**CROSS SECTION** 

6" MIN —

BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS

DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND

IMMEDIATELY. BERM SHALL BE PERMITTED. PERIODIC INSPECTION

THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH

SHALL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO

PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP

REPAIR OR CLEANOUT OF ANY MEASURES USED TO TRAP

AND MAINTENANCE SHALL BE PROVIDED AS NEEDED.

SEDIMENT, ALL SEDIMENT SPILLED, DROPPED, WASHED OR

TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED

STABILIZED CONSTRUCTION ENTRANCE

50' (MIN.)

FILTER

3" CRUSHED STONÉ

OR EGRESS OCCURS.

FABRIC

(MIN.)

**EXISTING** 

MOUNTABLE BERM

PAVEMENT

#### SEDIMENT SOCK / HAY WATTLE DETAIL NOT TO SCALE CATCH BASIN GRATE CATCH BASIN GRATIE SILTSACK SILTSACK 1" REBAR FOR **BAG REMOVAL BALED HAY** OR STRAW **EXPANSION RESTRAINT**

PLAN VIEW

1. INSTALL SILTSACK IN ALL CATCH BASINS WHERE INDICATED ON THE PLAN BEFORE COMMENCING WORK OR IN PAVED AREAS AFTER BINDER COURSE ID PLACED AND HAY BALES HAVE BEEN

2. GRATE TO BE PLACED OVER SILTSACK.

NOTES:

**SECTION VIEW** 

3. SILTSACK SHALL BE INSPECTED WEEKLY AND AFTER ALL STORM EVENTS AND CLEANING OR REPLACEMENT SHALL BE PERFORMED PROMPTLY AS NEEDED. MAINTAIN UNTIL UPSTREAM AREAS HAVE BEEN PERMANENTLY STABILIZED.

ENCLOSE STRUCTURE WITH HAYBALES IMMEDIATELY AFTER CATCH BASIN CONSTRUCTION. MAINTAIN UNTIL PAVING BINDER COURSE IS COMPLETE OR A PERMANENT STAND OF GRASS HAS BEEN ESTABLISHED.

2. IF GRATE IS AGAINST EXISTING CURB THEN HAY BALES ARE TO BE PLACED AROUND THREE SIDES OF GRATE ONLY.

GRATE TO BE PLACED OVER FILTER FABRIC.

CONSTRUCTION SEQUENCE NOTES:

INSTALL BUILDING FOUNDATION.

FILL SITE TO SUBGRADE

CONSTRUCT BUILDING.

**DISTURBED AREAS** 

INSPECTION SIGN-OFFS.

INSTALL SITE DRAINAGE AND UTILITIES.

CONSTRUCT PAVED AREA BASE COURSES.

BEFORE ANY STORMWATER DISCHARGE

EARTHWORK.

COMMENCE CLEARING, GRUBBING AND EARTHWORK

CUT AND DISPOSE OF ANY DEBRIS PRODUCED DURING

72 HOURS OF THE ESTABLISHMENT OF FINAL GRADE.

FINAL PAVING OF DRIVEWAY AND PARKING AREAS.

15. CONTRACTOR SHALL NOTIFY AND COORDINATE WITH ALL

INSTALL EROSION AND SEDIMENT CONTROLS AS SHOWN ON PLAN.

STABILIZE SIDE SLOPES. SIDE SLOPES MUST BE FULLY STABILIZED

DISTURBED AREAS SHALL BE PERMANENTLY STABILIZED WITHIN

INSPECT ALL SEDIMENT AND EROSION CONTROL MEASURES.

ALL TEMPORARY EROSION CONTROL CAN BE REMOVED.

AUTHORITIES RESPONSIBLE FOR INSPECTIONS. IT IS THE

CONTRACTOR'S RESPONSIBILITY TO OBTAIN ALL REQUIRED

INSTALL SITE LANDSCAPING AND PERMANENT SEEDING OF ALL

AFTER ALL SEEDED AREAS HAVE ESTABLISHED STABLE GROWTH,

BALES SHALL BE INSPECTED PERIODICALLY AND AFTER ALL STORM EVENTS. REPAIR OR REPLACEMENT SHALL BE PERFORMED PROMPTLY AS NEEDED.

#### **OPERATION AND MAINTENANCE:**

#### CONSTRUCTION PHASE

THE BMP's ASSOCIATED WITH THIS PROJECT WILL BE OWNED BY THE CONTRACTOR, WHO WILL BE RESPONSIBLE FOR INSPECTION, OPERATION AND MAINTENANCE. THE PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES

- 1. PRIOR TO ANY CONSTRUCTION, THE CONTRACTOR SHALL PHYSICALLY MARK THE LIMITS OF NO
- 2. THE CONTRACTOR IS TO INSTALL AND MAINTAIN DRAINAGE FACILITIES AS SHOWN ON THE SITE
- 3. PRIOR TO CONSTRUCTION, ALL EROSION/SILTATION CONTROL DEVICES SHOWN ON ABOVE PLAN ARE TO BE INSTALLED. TO PREVENT SILT INTRUSION INTO THE DRAINAGE SYSTEM DURING CONSTRUCTION. THE CONTRACTOR IS TO INSTALL AND MAINTAIN INLET PROTECTION AT ALL CATCH BASINS, AND SET A SILT FENCE OR SEDIMENT SOCK AT ALL SLOPES WHICH MAY ERODE IN THE DIRECTION OF ANY OPEN DRAINAGE FACILITIES. SUCH PREVENTIVE MEASURES ARE TO BE MAINTAINED THROUGHOUT THE CONSTRUCTION PROCESS. TEMPORARY CONTROLS SHALL BE INSTALLED TO REDUCE DUST AND SEDIMENT TRANSPORT.
- 4. CONSTRUCTION OF DRAINAGE FACILITIES IS TO BE INSPECTED BY DESIGN ENGINEER TO VERIFY CONFORMANCE TO THE DESIGN PLAN.
- 5. THE SEQUENCE OF DRAINAGE CONSTRUCTION SHALL BE AS FOLLOWS: A. CLEAR, GRUB, EXCAVATE AREAS FOR DRAINAGE SYSTEMS B. TRENCH AND INSTALL PIPES, CATCH BASINS MANHOLES C. INSTALL INLET PROTECTION.

LAND DISTURBANCE ON THE SITE AND INSTALL PERIMETER CONTROLS.

- 6. EROSION CONTROLS ARE TO BE INSPECTED AND MAINTAINED ON A WEEKLY BASIS OR AFTER EVERY HALF INCH OF RAIN FALL. UPON DISCOVERY OF SILT BUILD-UP IN ANY CATCH BASIN SUMPS. OR ANY OTHER STRUCTURES. THEY ARE TO BE CLEANED
- 7. ALL EXPOSED SOILS SHALL BE IMMEDIATELY STABILIZED WITH A LAYER OF MULCH HAY OR JUTE BLANKETS-AS NEEDED FOR SLOPES STEEPER THAN 3:1.
- 8. TEMPORARY WATER DIVERSION MUST BE USED AS NECESSARY UNTIL AREAS AREA STABILIZED. 8.1. DITCHES AND SWALES SHALL BE STABILIZED BEFORE DIRECTING WATER TO THEM
- 8.2. ROADWAYS AND PARKING LOTS SHALL BE STABILIZED BEFORE DIRECTING WATER TO THEM 8.3. CUT AND FILL SLOPES SHALL BE SEEDED/ LOAMED WITHIN 72 HOURS OF ACHIEVING FINISH
- 9. PRIOR TO CONSTRUCTION OF IMPERVIOUS AREAS, ALL DRAINAGE STRUCTURES AND PIPES SHALL BE INSTALLED AND INSPECTED FOR PROPER FUNCTION. DURING CONSTRUCTION OF OTHER SITE FEATURES, ALL DRAINAGE FACILITIES SHALL BE INSPECTED ON A WEEKLY BASIS AND CLEANED/REPAIRED IMMEDIATELY UPON DISCOVERY OF SEDIMENT BUILD-UP OR DAMAGE
- 10. AFTER PAVING IS INSTALLED, IT SHALL BE SWEPT CLEAN ON A REGULAR BASIS.
- 11. IF DEWATERING IS NECESSARY DURING CONSTRUCTION, THE WATER WILL BE TREATED FOR TOTAL SUSPENDED SOLIDS (TSS) REMOVAL PRIOR TO DISCHARGE TO RECEIVING WATER.

#### POST-DEVELOPMENT PHASE

THE OWNER(S) IS TO BE RESPONSIBLE FOR MAINTENANCE OF ALL DRAINAGE STRUCTURES IN THE PROJECT - INCLUDING ROOF DRAINS, DRAIN PIPES, CATCH BASINS, AND DRAIN MANHOLES

#### REGULAR MAINTENANCE IS TO INCLUDE THE FOLLOWING:

- INSPECTION OF ALL DRAINAGE FACILITIES (CATCH BASINS, PIPES, OUTLET CONTROL STRUCTURES, AND DETENTION BASINS) EVERY THREE MONTHS. DURING THESE INSPECTIONS, THE INSPECTOR (A REGISTERED PROFESSIONAL CIVIL ENGINEER QUALIFIED IN DRAINAGE SYSTEMS) SHALL LOOK FOR EVIDENCE OF THE FOLLOWING: STRUCTURAL DAMAGE. SILT ACCUMULATION (NEAR INLET INVERTS ON CATCH BASINS AND OUTLET CONTROL STRUCTURES), AND IMPROPER FUNCTION. A REPORT ON THE SYSTEM SHALL BE DELIVERED TO THE OWNER.
- 7. AFTER INSPECTION, IF ANY OF THE ABOVE CONDITIONS EXIST, THE INSPECTOR SHALL NOTIFY THE OWNER. WHO SHALL IMMEDIATELY ARRANGE FOR ALL NECESSARY REPAIRS AND/OR SEDIMENT
- 8. THE PAVEMENT AREA IS TO BE SWEPT CLEAN, AS REQUIRED (I.E., VISUALLY NOTICEABLE DEBRIS BUILD-UP). A MINIMUM OF ONCE PER YEAR.
- 9. ALL GRADED SLOPES SHALL BE INSPECTED EVERY SPRING FOR EROSION, UPON DISCOVERY OF ANY FAILURE (IE. EROSION), LOAM AND SEED SHALL BE PUT IN PLACE AND NURTURED.
- 10. DURING THE WINTER MONTHS, ALL SNOW IS TO BE STORED SUCH THAT SNOW MELT IS CONTROLLED WITHIN THE PAVED AREA.


WINTER CONSTRUCTION SEQUENCE NOTES ALL PROPOSED VEGETATED AREAS THAT DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1 AND SEEDING AND PLACING 3-4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORING NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.

3. AFTER OCTOBER 15, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3" OF

WARNER PLANNING BOARD CHAIRMAN:

#### EROSION CONTROL NOTES ((DURING CONSTRUCTION)

- 1. THE CONTRACTOR MUST INSTALL EIROSION CONTROL MEASURES AS SHOWN ON THE PLANS AND IN THE DETAILS PRIOR TO STARTING ANY OTHER WORK ON THE SITE. EROSION CONTROL MUST BE INSTALLED AT IEVERY INLET STRUCTURE (EXISTING AND PROPOSED) AND MAINTAINED FOR THE DURATION OF THE PROJECT.
- EROSION CONTROLS AS SHOWN OMIPLANS SHALL BE INSPECTED, REPAIRED AND/OR MAINTAINED BY THE CONTRACTOR DAILY AND WITHIN 12 HOURS OF EACH STORM EVENT.
- SEDIMENT DEPOSITS SHALL BE REMOVED WHEN THEY REACH A DEPTH OF 1/4 TO 1/2 THE HEIGHT OF THE SILT FENCE OR SEDIMENT SOCK.
- SEDIMENT SHALL BE CONTAINED WMITHIN THE CONSTRUCTION SITE, AWAY FROM DRAINAGE STRUCTURES. SEDIMENT REACHING THE PUBLIC WAY SHALL BE REMOVED BY STREET SWEEPING AND NOT BY FLUSHING
- STABILIZE SLOPES STEEPER THAN 3:1 (HORIZONTAL TO VERTICAL) WITH SEED, SECURED GEOTEXTILE FABRIC, OR ROCK RIPHRAP AS REQUIRED TO PREVENT EROSION DURING CONSTRUCTION.
- CLEAN OUT CATCH BASINS, DRAIN MANHOLES AND STORM DRAIN PIPES AFTER COMPLETION OF CONSTRUCTION.
- 7. LOAM AND SEED ALL DISTURBED AREAS. PERMANENT SEEDING SHALL OCCUR IN THE SPRING FROM LATE MARCH THROUGH MAY AND IN LATE SUMMER OR EARLY FALL BETWEEN AUGUST AND OCTOBER
- DUST SHALL BE CONTROLLED AT THE SITE WITH MECHANICAL WATER SPRAYING AS NECESSARY AND DURING EXTENDED DRY PERIODS.
- UPON ESTABLISHMENT OF PERMAMIENT VEGETATION OVER DISTURBED AREAS, REMOVE AND DISPOSE OF STRAW WATTLES AND STAKES.
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO MAINTAIN AND SUPPLEMENT THE SPECIFIED SEDIMENTATION CONTROLS AS NECESSARY TO PREVENT SEDIMENTATION OF OFF-SITE AREAS AND/OR ANY REGULATED RESOURCE AREAS. FAILURE BY THE CONTRACTOR TO CONTROL EROSION, POLLUTION AND/OR SILTATION SHALL BE CAUSE FOR THE OWNER TO EMPLOY OUTSIDE ASSISTANCE OR TO USE HIS OWN MEANS TO PROVIDE THE NECESSARY CORRECTIVE MEASURE. THE COST OF SUCH ASSISTANCE PLUS PROJECT ENGINEERING COSTS WILL BE THE CONTRACTOR'S RESPONSIBILITY.
- THE CONTRACTOR SHALL CHECK TIME CONDITION OF EROSION CONTROLS WEEKLY TO KEEP THEM IN GOOD OPERATING CONDITION. EROSION CONTROLS SHALL ALSO BE INSPECTED. REPAIRED AND MAINTAINED BY THE CONTRACTOR WITHIN 12 HOURS OF ANY STORM EVENT PRODUCING 1/2 INCH OF RAINFALL @R MORE, EROSION CONTROLS SHALL BE REPLACED WHEN DETERIORATED, OR WHEN ORDERED BY THE ENGINEER. SEDIMENT DEPOSITS SHALL BE REMOVED WHEN THEY REACH AIDEPTH OF 6 INCHES.
- 12. IN ADDITION TO THOSE LOCATIONS SHOWN ON THIS PLAN AND ON THE GRADING AND DRAINAGE PLANS, EROSION CONTROLS SHALL BE INSTALLED AT THE FOLLOWING LOCATIONS: TOE OF SLOPE OF EMISSANKMENT CONSTRUCTION, TOE OF TEMPORARY EARTHWORK STOCKPILES. STOCKPILE SIDE SLOPES SHALL NOT EXCEED 2:1.
- 13. EROSION AND SEDIMENTATION COMITROL SHALL BE IN COMPLIANCE WITH MASSACHUSETTS STORMWATER POLICY
- AN AREA SHALL BE CONSIDERED ST/ABLE IF OE OF THE FOLLOWING HAS OCCURRED: A. BASE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED. B. A MINIMUM OF 85% VEGETATED @ROWTH HAS BEEN ESTABLISHED. C. A MINIMUM OF 3" OF NON-EROSIWE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN
  - D. EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- 15. THE SMALLEST PRACTICAL AREA SIMALL BE DISTURBED DURING CONSTRUCTION BUT IN NO CASE EXCEED 2.75 ACRES AT ANY ONE TIME BEFORE DISTURBED AREAS ARE STABILIZED
- 16. ALL AREAS SHALL BE STABILIZED WMITHIN 90 DAYS OF INITIAL DISTURBANCE




SITE PLAN ROUTE 103 WEST, WARNER NH.

A\sSESSOR'S MAP 35 LOTS 4-1 & 4-2

COMET, ILLC

355 MIDDLESEX AVE, SUITE 7 WILMINGTON, MA 01887

**EXISTING CONDITIONS PLAN** CS8501



Ranger Engineering Group, Inc. 13 Branch Street, Suite 101 Methuen, MA 01844 Tel: 978-208-1762 ramgereng.com

2020-05-06

SCALE:

SHEET 16 OF 16

SILTSACK SEDIMENT TRAP NOT TO SCALE

FABRIC

CATCH BASIN SEDIMENT TRAP

8" (MIN.)

**CATCH BASIN** 

GRATE

Plan View

NOTES:

STAKES

FABRIC

1" X 1" X 3'

WOOD STAKE

4"EMBEDMENT

(2 PER BALE)

2. ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH OR WHICH ARE DISTURBED AFTER OCTOBER 15TH SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE FLOW.

CRUSHED GRAVEL PER NHDOT ITEM 304.3